

D



Réf. 4SC




Interior cleaning without obstacles.




OPTIONAL: TOWELBAR / SHELF-CRYSTAL see pages 275

- Overbath screen until 2100 mm.
- Pivot door (P2/P3) 180° inwards and outwards.
- 8 mm safety glass on the fixed panels (F1/F4) and 6 mm on the door (P2/P3).
- Fixed panels width (F1/F4) will change in relation with product total width.
- Central magnetic closing.
- 5 mm adaptation margin for out-of-true walls



WALL PROFILE



4SC



# D4 Pure20

PIVOT SIGLE

Pivot twin door 180° with 2 in-line panels, for bath in a recess or in a corner.

DIMENSIONS: Standard Height 1.500 mm. Standard In-line panel 180 mm

SPECIAL MANUFACTURING AND FINISHES			
DIMENSIONS: Special Heights between 1.400 - 1.600 mm Door and fixed segments width made-to-measure (join always a sketch)			
Width (mm) Enclosure between	in a recess	Glass Transparent	Glass screen Frosted
900 ↔ 1.000	<b>4SC</b>		
1.101 ↔ 1.300			
1.301 ↔ 1.500			
1.501 ↔ 1.700			
1.701 ↔ 1.900			
1.901* ↔ 2.100			

\* Fix panel F1/F4 width 180mm. From 1.901mm, the increase of dimension will be applied on the fix panels.

ADJOINING IN-LINE PANEL ESPECIAL 90° Heights between 300 - 2.100 mm. (join always a sketch)			
Ancho (mm)	Left	Right	
200 ↔ 500	<b>4MI</b>	<b>4MD</b>	
501 ↔ 1.000			
1.001 ↔ 1.200			

PRICE INCREASING	
DUSCHOLUX CareTec® Pro Glass Protection coating on the door	
DUSCHOLUX CareTec® Pro Glass Protection coating on the in-line panel	
Adjustments on the glass: (send sketch, please consult)	
Coloured Glass	

**FROSTED GLASS SCREEN, SEE PAGES 280 - 285**

PERSONALIZED V6U - SURCHARGE +30% (Price glass screen Frosted)

Example combination in-line panel.

